

# Wind 150


Extract fans

- Casing material: Plastic

| | Unit of measurement | Wind 150 |
|---|---|---|
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50 |
| Maximum airflow | m³/h | 295 |
| Ingress protection rating | - | IP24 |
| Impeller material | - | Plastic |

## Dimensions

| a | b | e | c | D |
|---|---|---|---|---|
| 210 | 195 | 66 | 60 | 150 |



## Ecodesign

| | | | | | | |
|---|---|---|---|---|---|---|
| Trademark | Blauberg | | | | | |
| Model | Wind 150 | | | | | |
| Specific energy consumption (SEC) (kWh/(m²/a)) | Cold | | Average | | Warm | |
| | -33.6 | B | -17.2 | E | -7.8 | F |
| Type of ventilation unit | Unidirectional | | | | | |
| Type of drive installed | Multi-speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Maximum flow rate (m³/h) | 295 | | | | | |
| Electric power input (W) | 26 | | | | | |
| Reference flow rate (m³/s) | 0.057 | | | | | |
| Specific power input (SPI) (W/(m³/h)) | 0.057 | | | | | |
| Control typology | Manual control | | | | | |
| Maximum external leakage rates (%) | 2.7 | | | | | |
| Airflow sensitivity at +20 Pa and -20 Pa (%) | 0.15 | | | | | |
| The indoor/outdoor air tightness (m³/h) | 1 | | | | | |
| Declared typology | RVU UVU | | | | | |
| Sound power level (dB(A)) | 61 | | | | | |
| The annual heating saved (AHS) (kWh/a) | Cold | | Average | | Warm | |
| | 3355 | | 1715 | | 776 | |